

WABCO Fitting Case

Couplings for commercial vehicles



Our fittings case 893 000 200 0 is ideal for any workshop or service vehicle with all major threaded fittings ready to use and very well organised.

- 26 different couplings often required for repairing or replacing compressed air equipment
- All couplings clearly marked within the case for easy identification.
- Less down time and interruptions of work.
- Fittings can be individually ordered through WABCO to re-stock the case.
- Containing New Line fittings.

Content Fitting Case 893 000 200 0

Push-in couplings		M 12 x 1.5	M 16 x 1.5	M 22 x 1.5	
<p>"New Line"</p>	Ø 6 x 1.0		4 x		
	Ø 8 x 1.0	8 x New Line	6 x New Line		
	Ø 10 x 1.0		6 x	6 x	
	Ø 12 x 1.5		6 x New Line	8 x New Line	
	Ø 15 x 1.5			4 x New Line	
	Ø 16 x 2.0			4 x	
	Ø 18 x 2.0			4 x	
Quick connections P5		M 12 x 1.5	M 16 x 1.5	M 22 x 1.5	M 16 x 1.5 female thread
	P5	4 x	6 x	4 x	
	P5 / 45° Elbow				4 x
	P5 / 90° Elbow				4 x
	P5 / L union				4 x
	P5 / T union				4 x
	P5 / F union				2 x
Conventional couplings			M 16 x 1.5	M 22 x 1.5	M 16 x 1.5 female thread
	M 22 x 1.5		3 x	3 x	
	M 16 x 1.5 female thread				8 x
Connection couplings		M 12 x 1.5	M 16 x 1.5	M 22 x 1.5	
	Screw plug	4 x	4 x	4 x	
	Pressure test connection		4 x	4 x	

Push-in fittings | for commercial vehicles

Threaded fittings with “New Line” technology



Ø I O	M 12 x 1.5	M 16 x 1.5	M 22 x 1.5
8 x 1.0	893 800 007 2	893 800 001 2	893 800 005 2
12 x 1.5	–	893 800 002 2	893 800 008 2
15 x 1.5	–	–	893 800 004 2
16 x 2.0	–	–	893 800 003 2

Pneumactical devices are fitted with all threaded fittings. During the installation, the respective plastic pipe is simply inserted into the threaded fitting. A retainer ring with a barbed effect holds the pipe in place, an additional O-ring in the threaded fitting ensures a good seal.

After years of using fittings with New Line technology on Trailer EBS E modulators and other devices, we are convinced of the sturdiness and security of these insert fittings.

Besides the low weight, these fittings are easily disassembled and are completely re-usable in the threaded fitting and the inlet.

- Low weight
- Easy to disassemble
- Re-usable in the threaded fitting and the inlet

Removal tools



Ø I O	Removal tool set 899 700 920 2	Metal removal tool
8 x 1.0	10 x 899 700 001 4	899 700 012 4
12 x 1.5	10 x 899 700 002 4	899 700 014 4
15 x 1.5	5 x 899 700 003 4	899 700 015 4
16 x 2.0		899 700 016 4

To release the fitting, a dismantling tool in the form of a split, fine sleeve is inserted between the pipe and the retainer ring. The sleeve holds in the retainer ring and

the pipe can be pulled out of the sleeve. The threaded fitting can usually be re-used for several years, as long as the seal does not harden.



WABCO Vehicle Control Systems (NYSE: WBC) is a leading supplier of safety and control systems for commercial vehicles. For over 140 years, WABCO has pioneered breakthrough electronic, mechanical and mechatronic technologies for braking, stability, and transmission

automation systems supplied to the world's leading commercial truck, trailer, and bus manufacturers. WABCO is headquartered in Brussels, Belgium.

For more information, visit www.wabco-auto.com